SAFETY DATA SHEET



1. Identification

Product Identifier Aquatone Solvent Base Enhancing Sealer

Other means of identification

Product code 2460

Recommended use Color enhancing solvent based sealer for

stone and grout.

Recommended restrictions Professional use only.

Manufacturer/Distributor/Supplier/Importer information

Company name Apeiron Stone & Concrete Care Inc.

Address P.O. Box 57

Mount Vernon, VA

22121

Telephone (703) 780-0254

Emergency phone number ChemTel (800) 255-3924

24 hour Emergency (800) 255-3924

2. Hazard(s) Identification

Physical hazardsFlammable LiquidsCategory 3Health hazardsEye irritationCategory 2A

None.

Aspiration Hazard Category 1

Environmental hazards Not classified.

OSHA defined hazards

Label elements



Signal word Danger

Hazard statement Flammable liquid and vapor.

Causes serious eye irritation.

May be fatal if swallowed and enters airways.

Precautionary statement

Prevention Keep away from heat/sparks/open flames/ hot surfaces. No smoking. Keep container

tightly closed. Ground/bond container and receiving equipment. Use explosion-proof electrical/ventilating/lighting/equipment. Use only non-sparking tools. Take

precautionary measures against static discharge. Wear protective gloves/ eye protection/

face protection. Wash hands and exposed skin thoroughly after handling.

Response IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with

water/shower. In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. IF SWALLOWED: Immediately call a POISON CENTER/doctor/medical

professional. Do NOT induce vomiting.

Store in a well-ventilated place. Keep cool. Store locked up.

Disposal Dispose of contents/container in accordance with local/regional/national/international

regulations.

Hazard(s) not otherwise

classified (HNOC)

None.

Supplemental information None

3. Composition/information on ingredients

Mixtures

Chemical name	CAS number	%
Hydrotreated heavy naphtha	64742-48-9	70-80
Telomer B monoether with polyethylene glycol	65545-80-4	1-10
Other components below reportable levels		20-30

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact Remove contaminated clothing immediately and wash skin with soap and water. In case of

eczema or other skin disorders: Seek medical attention and take along these instructions.

Eye contact Rinse with water for at least 15 minutes. Remove contact lenses if present and easy to do so.

Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur. Only induce vomiting at the

Dermatitis. Rash. May cause an allergic skin reaction.

instruction of medical personnel.

Most important

symptoms/effects, acute and

delayed

Indication of immediate medical attention and special

treatment needed

Provide general support measures and treat symptomatically. Thermal burns: Flush with water immediately. While flushing, remove clothes which do not adhere to affected area. Call

an ambulance. Continue flushing during transport to the hospital. Keep victim under

observation. Symptoms may be delayed.

General information Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media Water fog. Foam. Carbon dioxide (CO₂). Dry chemical powder, sand, or earth may be used for

small fires only.

Unsuitable extinguishing

media

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

Vapors may form explosive mixtures with air. Vapors may travel considerable distance to a source or ignition and flash back. This product is a poor conductor of electricity and can become electrostatically charged. If sufficient charge is accumulated, ignition of flammable mixtures can occur. To reduce potential for static discharge, use proper bonding and grounding procedures. During fire, gases hazardous to health may be formed.

Special protective equipment

and precautions for

firefighters

Self-contained breathing apparatus and full protecting clothing must be worn in case of fire.

Fire-fighting

equipment/instructions

In case of fire and/or explosion do not breathe fumes. Move containers from fire area if you

can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

General fire hazards Flammable liquid and vapor.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Keep out of low areas. Wear appropriate protective equipment and clothing during clean-up. Avoid inhalation of vapors or mists. Ensure adequate ventilation. Remove all sources of ignition. Local authorities should be advised if significant spillages cannot be contained. For personal

protection, see section 8 of the SDS.

Methods and materials for containment and cleaning up

Eliminate all ignition sources. Use only non-sparking tools. Take precautionary measures against static discharge. Keep combustibles away from spilled material.

Large spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Cover with plastic sheet to prevent spreading. Absorb in vermiculite, dry sand or earth and place into containers. Prevent entry into waterways, sewer, basements or confined areas. Following product recovery, flush area with water.

Small spills: Absorb with earth, sand, or other non-combustible material and transfer to container for later disposal. Clean surface thoroughly to remove residual contamination.

Never return spills to original container for re-use. For waste disposal, see section 13 of the

Environmental precautions

Avoid release to the environment. Avoid discharge into areas not consistent with package labeling.

7. Handling and storage

Precautions for safe handling Do not handle, store or open near

Do not handle, store or open near an open flame, sources of heat or sources of ignition. Do not smoke. Use explosion proof equipment and non-sparking tools. Take precautionary measures against static discharge. Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Observe good industrial hygiene practices.

Conditions for safe storage, including any

Keep away from heat, sparks and open flame. Ground/bond container and equipment. Store in original tightly closed container. Store away from incompatible materials (see section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

No information.

incompatibilities

Biological limit values

No information.

Appropriate engineering

controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits.

Individual protection measures, such as personal protective equipment

Eye/face protection Avoid contact with eyes. Wear safety glasses with side shields (or goggles).

Skin protection

Hand protection Wear appropriate chemical resistant gloves

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment. **Thermal hazards** Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

When using do not smoke or use chewing tobacco. Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.

Contaminated work clothing should not be allowed out of the workplace.

9. Physical and chemical properties

Appearance

Physical StateClear liquid.ColorLight amber.

Odor Characteristic.
Odor threshold Not available.
pH Not available.
Melting/freezing point Not available.

Initial boiling point and

300-410°F (148.9-210°C) estimated.

boiling range

Flash point 100°F (37.8°C) estimated.

Evaporation rate Not available.
Flammability Not available.

Flammability Limits

Upper 6% estimated.
Lower 0.7% estimated.
Vapor pressure Not available.
Vapor density Not available.

Specific gravity (water=1) 0.85
Solubility in water Insoluble.
Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperature 540°F (282.2°C) estimated.

Decomposition temperature Not available. **Viscosity** Not available.

10. Stability and reactivity

ReactivityThis product is stable and non-reactive under normal conditions of use. **Chemical stability**Material is stable under normal conditions. Store in a cool dark place.

Possibility of hazardous

Hazardous polymerization does not occur.

reactions

Conditions to avoid Avoid heat, sparks, open flames and other ignition sources. Avoid temperatures exceeding the

flash point. Contact with incompatible materials.

Incompatible materials Oxidizing agents, acids.

Hazardous decomposition

Carbon dioxide, carbon monoxide.

products

11. Toxicological information

Information on likely routes of exposure

IngestionExpected to be low ingestion hazard.InhalationProlonged inhalation may be harmful.

Skin contact May cause mild skin irritation.

Eye contact Causes serious eye irritation. Wear eye/face protection.

Symptoms related to the Dermatitis. Rash.

physical, chemical and toxicological characteristics

Acute toxicity Not established.

Product	Route and Species	LD50		
Aquatone Solvent Base Enhancing Sealer (CAS mixture)				
Acute	Oral, rat	>5.000 mg/kg estimated		

^{*}Estimates for product may be based on additional component data not shown

Skin corrosion/irritation Not classified.

Serious eye damage/ Causes serious eye irritation.

irritation

Respiratory sensitization Not available. **Skin sensitization** Not available.

Germ cell mutagenicity No data available to indicate product or any components present at greater than 0.1% are

mutagenic or genotoxic.

Carcinogenicity This product is not expected to be a carcinogen.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not Listed.

Reproductive toxicity This product is not expected to cause reproductive or developmental effects.

Specific target organ toxicity

Not classified.

single exposure

Specific target organ toxicity

Not classified.

- repeated exposure

Aspiration hazard May be harmful or fatal if product enters airways.

12. Ecological information

Ecotoxicity

=			
Product	Species	Test Results	
Aquatone Solvent Base En	hancing Sealer (CAS mixture)		
Aquatic			
Crustacea	Daphnia	EC ₅₀ (48 hr): 206 mg/L estimated	
Fish	Fathead minnow	LC ₅₀ (96 hr): 90 mg/L estimated	

^{*}Estimates for product may be based on additional component data not shown

Persistence and degradability No data available.

Bioaccumulative potential Potential to bioaccumulation is expected to be low.

Mobility in soil No data available.

Other adverse effects Harmful to aquatic life. May cause long lasting harmful effects to aquatic life.

13. Disposal considerations

Disposal instructionsCollect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of

contents/container in accordance with local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the

waste disposal company.

Waste from residues/unused

product

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner. (see:

Disposal instructions).

Contaminated packaging Empty containers should be taken to an approved waste handling site for recycling or

disposal. Since emptied containers may contain product residue, follow label warnings even

after container is emptied.

14. Transport information

DOT

UN number UN1993

UN proper shipping name Flammable liquid, n.o.s. (Contains: Petroleum Hydrocarbons)

Transport hazard class(es)

Class 3 **Subsidiary risk Packaging group** Ш

Special precautions for

Read safety instructions, SDS, and emergency procedures before handling.

This product is not intended to be transported in bulk.

user

Marine pollutant No

Special precautions for user

Transport in bulk according to Annex II of MARPOL 73/78

and the IBC Code

DOT



15. Regulatory information

US federal regulations

SARA 302 Extremely hazardous substance

Not listed.

SARA 304 Emergency release notification

Not listed.

SARA 311/312 Hazard Categories

Immediate Hazard - Yes Delayed Hazard - No Fire Hazard - Yes Pressure Hazard - No Reactivity Hazard - No

SARA 313 (TRI reporting)

Not listed.

16. Other information, including date of preparation or last revision

Issue date 4/14/2015 4/14/2015 **Revision date**

Version # 1

HMIS® ratings Health: 1

> Flammability: 2 Physical hazard: 0

NFPA ratings Health: 1

> Flammability: 2 Instability: 0

Disclaimer The information provided in this Safety Data Sheet is correct to the best of our knowledge,

and have been obtained from resources believed to be reliable. The information given is

designed only as a guidance for safe handling, use, processing, storage, transportation, disposal, and release and is not to be considered a warranty or quality specification. The information related only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified by the text.

Revision information

First issue